

ARP:
50°16'04"N
028°44'37"E

AFIS 119.750

	SURFACE	STRENGTH	WIDTH
APRON	ASPHALT CONCRETE	PCN 18/F/D/Y/T	16 m 7 m
TWY 1	ASPHALT CONCRETE	PCN 20/F/D/Y/T	
TWY 2	ASPHALT CONCRETE	PCN 20/F/D/Y/T 5250kg/0.5Mpa	

VAR 6° E

NOT TO SCALE

DECLARED DISTANCES

RWY	TORA	TODA	ASDA	LDA
13	1650	1850	1650	1650
31	1650	1850	1650	1650

APRON

1

2

3

4

CWY 200x150

ELEV 219.9

TWY 2

TWY 1

"Aviatik" Club

13

31

0.024%

219.9 m

220.3 m

STRIP 2050x150

ARP

1650x35 ASPHALT CONCRETE

ELEV 220.3

31

CWY 200x150

AFTER LANDING

BEFORE TAKE-OFF

RWY	DIRECTION (TRUE)	THR	BEARING STRENGTH	AERODROME LIGHTING: NIL
13	135°09'	50°16'23"N 028°44'07"E	PCN 20/F/D/Y/T	
31	315°09'	50°15'45"N 028°45'06"E	PCN 20/F/D/Y/T	

ELEVATIONS AND DIMENSIONS IN METRES,
BEARINGS ARE MAGNETIC

CHANGE: New chart.

State Aviation Administration

[AIRAC AMDT 02/16]